

## Declaration of Performance

**Reference Number:** RR/0001RMS

**Factory Production Control Certificate Number:** 0836-CPR-13/F049

**1. Product Groups:**

Lightweight Capsheet Mineral, Traditional Capsheet Mineral, Sand Shed Felt & Lightweight Bonding, Traditional Bonding

**2. Unique Product Names / Codes:**

Name	Code	Weight (kg)	Length (m)
5m Sand Shed Felt	B**7**5F	7kg	5m
14kg Bonding Sand	B*14*10F	14kg	10m
18kg Bonding Sand	B*18*10F	18kg	10m
25kg Bonding Sand	B*25*10F	25kg	10m
Lightweight Capsheet Mineral	M*29G10F	29kg	10m
Capsheet Mineral (Green, Red, Blue-Grey, Mixed Brown)	M*34G10F	34kg	10m
38kg Mineral (1E) (Green, Red, Blue-Grey, Mixed Brown)	M*38G10F	38kg	10m

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

Roof waterproofing. Recycled rag fibre based oxidised roofing membranes finished with a coloured slate mineral or sand upper surface. For use as garden outbuilding weatherproofing layer or as underlays, intermediate layers and cap sheets / top layers in a traditional built up flat roof system, adhered with hot poured bitumen.

**4. Manufacturer:**

Rose Roofing Limited  
1 Flass Lane  
Cutsyke  
Castleford  
West Yorkshire  
WF10 5JW  
United Kingdom

**5. Authorised Representative:**

Not applicable

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V of the CPR:**

System 2+

**7. Notified Body:**

The British Board of Agreement (BBA) performed an initial inspection of the manufacturing plant and factory production control, and performs continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of factory production control with reference to **BS EN 13707:2013** and **CPR 305/2011/EU**.

**8. Not applicable.**

**9. Declared Performance:**

Essential Characteristic	Specific Test ref.	Declared Performance	Harmonised Standard(hEN)
Watertightness	BS EN 1928 method a.	PASS	BS EN 13707:2013
Straightness	BS EN 1848-1	PASS	as above
Width	BS EN 1848-1	PASS	As above
Visible Defects	BS EN 1850-1	PASS	as above
External Fire Performance	BS EN 13501-5	F <sub>ROOF(t4)</sub>	as above
Reaction to Fire	BS EN 13501-1	F	as above

For product variable essential characteristics such as length, mass per unit area, tensile strengths and nail tear please refer to that individual product's data sheet.

**10. The performance of the product identified in 1. and 2. above is in conformity with the declared performance stated in 9.**

Signed by and on behalf of the manufacturer by:

**Nick Sykes**  
Operations Director  
Castleford, November 2013



---