

Declaration of Performance

Reference Number: RR/0004PPO

Factory Production Control Certificate Number: **0836-CPR-13/F049**

1. Product Groups:

180 Polyester Sand, 180 Polyester Mineral, 250 Polyester Sand, 250 Polyester Mineral, 350 Polyester Sand, 350 Polyester Mineral, Polyester Underlay, High Performance Underlay.

2. Unique Product Names / Codes:

Name	Code	Weight (kg)	Length (m)
Polyester Underlay	P125S16F	29kg	16m
180 Polyester Sand	P180S20F	36kg	20m
180 Polyester Mineral	P180G10F	34kg	10m
250 Polyester Sand	P250S20F	40kg	20m
250 Polyester Mineral	P250G10F	40kg	10m
350 Polyester Sand	P350S10F	34kg	8m
350 Polyester Mineral	P350G10F	38kg	8m

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Roof waterproofing. Polyester based oxidised bitumen roofing membranes finished with a coloured coarse slate mineral or sand upper surface. For use as underlays, intermediate layers, and capsheets as part of a traditional built up roof system for both domestic and commercial properties. Adhered with hot poured bitumen.

4. Manufacturer:

Rose Roofing Limited
1 Flass Lane
Cutsyke
Castleford
West Yorkshire
WF10 5JW
United Kingdom

5. Authorised Representative:

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in the Annex V of the CPR:

System 2+

7. Notified Body:

The British Board of Agreement (BBA) performed an initial inspection of the manufacturing plant and factory production control, and performs continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued a certificate of conformity of factory production control with reference to **BS EN 13707:2013** and **CPR 305/2011/EU**.

8. Not applicable.

9. Declared Performance:

Essential Characteristic	Specific Test ref.	Declared Performance	Harmonised Standard(hEN)
Watertightness	BS EN 1928 method a.	PASS	BS EN 13707:2013
Straightness	BS EN 1848-1	PASS	as above
Visible Defects	BS EN 1850-1	PASS	as above
External Fire Performance	BS EN 13501-5	F _{ROOF(t4)}	as above
Reaction to Fire	BS EN 13501-1	F	as above

For product variable essential characteristics such as length, mass per unit area, tensile strength and nail tear please refer to that individual product's data sheet.

10. The performance of the product identified in 1. and 2. above is in conformity with the declared performance stated in 9.

Signed by and on behalf of the manufacturer by:

Nick Sykes
Operations Director
Castleford, November 2013


