



The need to fire protect timber or plywood to be used in construction usually comes from the requirement to achieve compliance with UK Building Regulations. Whilst cost and lead times are often key considerations at procurement stage, a careful assessment of product performance credentials by all concerned in the supply chain is fundamental to ensure a building remains fire safe during its many years of service.

**Specified and used with confidence around the world for many years, DRICON fire protection has never failed to give that all important time in a fire situation.**

**Questions you should ask about your fire retardant treatment...**



Other INT2 fire retardant impregnation treatments	Fire Protection COATING products
---------------------------------------------------	----------------------------------

 <p><b>Is it an INT2, humidity resistant type fire treatment, commercially applied via a high pressure impregnation process, with over 35 years of proven performance globally?</b></p>	✓	✗	✗
 <p><b>Is it accredited by the British Board of Agrément (BBA)?</b> BBA is the UK's major approval body for construction products. The BBA logo validates the claims a manufacturer makes regarding the performance and durability of its fire treatment and demonstrates its fitness for purpose. <b>DRICON is the only BBA accredited fire retardant treatment for timber.</b></p>	✓	✗	✗
 <p><b>Does it hold UK Wood Protection Association Approved status?</b> This involves a rigorous assessment of fire performance data by an independent panel of experts appointed by the WPA.</p>	✓	?	✗
 <p><b>Is it Approved for use by London Underground?</b> Listed on the London Underground Product Register and fully compliant with LUL Standard 1-085 'Fire Safety Performance of Materials'.</p>	✓	?	?
 <p><b>Is it accepted by the National Scaffold Board Association (NASC)?</b> For the fire protection of scaffold boards used in high risk environments such as oil rigs.</p>	✓	?	?
<p><b>Are independent Euroclass B Classification Reports available?</b> For a range of timber cladding and plywood species enabling use with or without an air gap in line with BS EN 13501-1.</p>	✓	?	?
<p><b>Is it compliant with current European Fire Retardant Durability Standards?</b> Which supports a maintenance free fire performance in excess of 30 years when used internally making it suitable for a wide range of internal cladding timber and plywood species without the need for a protective coating.</p>	✓	?	?
<p><b>Does it have the ability to significantly reduce smoke emission in a fire situation?</b> In line with the requirements of UK Building Regulations ensuring vital time for people to safely escape from a burning building.</p>	✓	?	?
<p><b>Is it non-hygroscopic?</b> Having the ability to remain very stable in the treated material for many years even at high levels of humidity ensuring it will not solubilise over time and migrate to the surface resulting in a progressive loss of fire performance.</p>	✓	?	?
<p><b>Is it applied by an ISO 9001 and ISO 14001 accredited company?</b></p>	✓	?	?

for more information on fire retardant treatments please visit [www.lonzafiretreatments.eu](http://www.lonzafiretreatments.eu)

# Lonza

Lonza Wood Protection  
Wheldon Road, Castleford, West Yorkshire, WF10 2JT.  
Tel: +44 (0)1977 714000 Fax: +44 (0)1977 714001  
E-Mail: [timberprotectionadvice.ukca@lonza.com](mailto:timberprotectionadvice.ukca@lonza.com)

© Copyright July 2018 Lonza.  
™ Dricon is a registered trademark of Arch Timber Protection, a Lonza company.  
Disclaimer: Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, Lonza gives no undertaking to that effect and no responsibility can be accepted for reliance on this information. Lonza updates its literature as and when necessary.  
Please ensure you have an up to date copy.