



**To specify DRICON fire retardant treated timber or panel products the following wording is recommended...**

The timber as detailed . . . (*insert species, type, grade, quantity, dimensions*) . . . is to be used in . . . (*insert end use description or description of component*) and is to be vacuum pressure impregnated with DRICON fire retardant and subsequently kiln dried in accordance with the DRICON manufacturer’s specification to meet . . . (*enter appropriate standard and treatment class*).

Treated timber which is subsequently rip sawn, equalised, planed or heavily sanded must be returned to the treatment plant for re-treatment.

**Treated Timber User Guide**

A DRICON Treated Timber User Guide with full information on all aspects of the use of DRICON fire retardant treated timber is available from Lonza on request.

**SPECIES AND THICKNESSES**

A full list of timber species available for DRICON fire retardant treatment, all backed with independent Classification Reports, is shown overleaf.

**ORDERING/DELIVERY**

Details for placing orders and arranging deliveries of DRICON fire retardant treated timbers are available direct from Lonza - tel: 01977 714000.

**PLEASE NOTE:**

Because of the safety aspect of fire protection we would recommend that specifiers contact Lonza Wood Protection directly to ensure you are specifying the correct species, thicknesses and level of protection.

**For more information on fire retardant treatment visit**

**[www.lonzafiretreatments.eu](http://www.lonzafiretreatments.eu)**



# Lonza

Lonza Wood Protection  
Wheldon Road, Castleford, West Yorkshire, WF10 2JT.  
Tel: +44 (0)1977 714000 Fax: +44 (0)1977 714001  
E-Mail: timberprotectionadvice.ukca@lonza.com